

MULTIPLE PROTECTION

WITH STRONG STABILITY AND HIGH SERVICE LIFE

精能绿能 精品精质

WHAT function SHOULD BE



✓ SOLAR COUNTER- ATTACK

✓ OPEN AFTER LONG-TERM USE BATTERY PROTECTION

✓ BATTERY REVERSE CONNECT BATTERY PROTECTION

✓ OVERVOLTAGE, WIND SPEED AND OVERLOAD PROTECTION

PRODUCT FEATURES

- 01 » PWM uninstal:
- 02 » Many kinds of charging modes
- 03 » Short circuit protection function:
- 04 » Digital intelligent control
- 05 » LCD + LED display parameters
- 06 » Wind/solar charge control:
- 07 » High stability
- 08 » Overheating protection function
- 09 » Wind and photovoltaic(PV)separate control



CONNECTION DIAGRAM



PRODUCT PARAMETERS

WELCOME TO OUR SHOP! 商品信息

Model No.	JN-WD24	JN-WD48	JN-WD96	JN-WD120	JJN-WD240
Wind turbine power	1kw	1kw 2kw 3kw 5kw	2kw 3kw 5kw 10kw	3kw 5kw 10kw	3kw 5kw 10kw
Solar max power	300w 600w 1000w	300w 600w 1000w 1500w	600w 1000w 1500w 3000w	1000w 1500w 3000w	1000w 1500w 3000w
Over-charge voltage	28.8v	57.6v	116v	144v	288v
Over-charge recovery voltage	26v	56v	110v	138v	264v
Method of control	PWM				
Free-load lost power	≤6mA				
Voltage lost on charging	≤0.26V				
Voltage lost on discharge	≤0.15V				
Environment temperature	-25°C - +55°C				
Shape Dimension	440mm×366mm×166mm				
Dump-load Dimension	400mm×230mm×290mm				
Net Weight	8KG				
Cooling Way	Cooling Fan				