

**NU-185A1H/R1H**

|   |                                      |
|---|--------------------------------------|
| - Cell Material   | 185 Watt                             |
| - Number Of Cells   | 48 in series                         |
| - Cell Type   | Square 155 mm, Multi-Crystal silicon |
| - Maximum power   | 190 Watt                             |
| - Minimum power   | 182 Watt                             |
| - Open Circuit Voltage (Voc)                                  | 30.2 Volt                            |
| - Short Circuit Current (Isc)                                 | 8.54 Ampere                          |
| - Maximum Power Voltage (Vpm)                                 | 24 Volt                              |
| - Maximum Power Current (Ipm)                                 | 7.71 Ampere                          |
| - Weight  | 15.5 Kg                              |
| - Dimension (HxWxD)   | 1.318 x 994 x 46 mm                  |
| - Module Efisiensi  | 14.2 %                               |
| - Max System Voltage  | 1000 Volt                            |
| - Frame Material  | Anodized Aluminium Alloy             |
| - Front Cover Material  | Low Iron Tempered Glasses            |
| - Encapsulation Material                                      | EVA Ethylene Vinyl Acetar) Resin     |
| - Bypass Diode  | Installed in The Terminal Box        |
| - BPPT (Badan Pengkajian dan Penerapan Teknologi) Certificate |                                      |

